

Auto-Reclosed RCCB

AUTO RECLOSED RCCB main function is to automatically reclose the circuit when a nuisance tripping is detected.

Depending on the number of resetting and the delay reset time selected, the user has a wide choice to selectively pre-set the system according to their requirement by simply turning the selector knob for no. of resetting and delay reset located on the control panel.



SPECIFICATION

Type/Model	DAR330
Rated Voltage	230V+10%, -15%
Frequency Range	50-60Hz
Power Consumption at Rest	S1.5VA
Insulation Voltage	2500V per min
Number of Automatic Reclosing	Selectable: 0-1-3-5-7 times
Delay Reset Time for Activating Auto Recloser	Selectable: 10-30-60-120-180 sec
Trip Counter Display	Digital red LED, 10mm x 5mm display
Trip Counter Reset Facility	Push button
By-Pass Facilities	By pass switch in front of motorized recloser

Dynamic Traffic System Sdn Bhd
No 52, Jalan Seroja 5D/2
Bukit Sentosa 48300 Rawang,
Selangor, Malaysia.

✉ sales@dynasystem.info

🌐 www.dynatech.my

NOTE: In keeping our policy of continuing product improvement, DynaTech reserves the right to change materials, design and specifications without prior notice.

AUTHORIZED AGENT

